

製品記号	ベルト巾	D2	l2	m2	n2	A	B	t	T	C	F	M	H	e × f	ベアリング	重量kg
OKVR-40	400	89.1	210	640	60	690	110	4.5	20	450	214	74	54	15×25	6204	12.3
OKVR-45	450		240	690		740				510	215	75	53			13.0
OKVR-50	500		270	740		790				570	216	76	51			13.7
OKVR-60	600		320	840		890				670	218	78	49			15.1
OKVR-75	750	114.3	415	1040	1090	857	246	69	32	23.0						
OKVR-90	900		490	1190	1240	1006	249	73	29	25.5						
OKVR-105	1050	139.8	565	1340	100	1390	150	6	25	1163	296	83	32	6205	38.5	
OKVR-120	1200		640	1490		1540				1313	311	86	29		46.7	
OKVR-140	1400	165.2	750	1730	120	1790	180	6		1530	358	108	41	19×30	6206	65.7
OKVR-160	1600		850	1930		1990				1729	370	112	36			88.5
OKVR-180	1800		980	2220	2290	1988	395	116	29	100.7						
OKVR-200	2000		1080	2420	2490	2187	400	121	25	109.1						

Product symbol	Belt width	D2	l2	m2	n2	A	B	t	T	C	F	M	H	e × f	Ball bearing	Weight(kg)
OKVR-40	400	89.1	210	640	60	690	110	4.5	20	450	214	74	54	15×25	6204	12.3
OKVR-45	450		240	690		740				510	215	75	53			13.0
OKVR-50	500		270	740		790				570	216	76	51			13.7
OKVR-60	600		320	840		890				670	218	78	49			15.1
OKVR-75	750	114.3	415	1040	1090	857	246	69	32	23.0						
OKVR-90	900		490	1190	1240	1006	249	73	29	25.5						
OKVR-105	1050	139.8	565	1340	100	1390	150	6	25	1163	296	83	32	6205	38.5	
OKVR-120	1200		640	1490		1540				1313	311	86	29		46.7	
OKVR-140	1400	165.2	750	1730	120	1790	180	6		1530	358	108	41	19×30	6206	65.7
OKVR-160	1600		850	1930		1990				1729	370	112	36			88.5
OKVR-180	1800		980	2220	2290	1988	395	116	29	100.7						
OKVR-200	2000		1080	2420	2490	2187	400	121	25	109.1						